

Claims

- [c1] A weld wire comprising:
a sheath encapsulating a metal core made of powdered metal, wherein a fill percentage of the metal core is higher than approximately 12%; and
the metal core having a core composition alloyed with an alloying element or an combination of elements comprising Cr, Mo, V, W, Hf and Nb or combinations thereof, wherein a total weight percentage of the alloying element or the combination of elements in the core composition does not exceed approximately 1%.
- [c2] 2.The weld wire of Claim 1, wherein the alloying element is Mo in the amounts selected from the range of about 0 to about 0.5 percent by weight.
- [c3] 3.The weld wire of Claim 1, wherein the fill percentage of the metal core is selected from the range of about 12% to about 30 %.
- [c4] 4.The weld wire of Claim 1, wherein the total percentage of the combination of elements is selected from the range of about 0.4% to about 0.8%.
- [c5] 5.The weld wire of Claim 1, wherein the composition mainly comprises,
approximately,

C 0.021–0.043%,
Mn 1.0–1.69.0%,
Si 0.33–0.66%, and
Ni 0.016–0.033%

and the fill percentage of the metal core is higher than approximately 12%.
- [c6] 6.The weld wire of Claim 1, wherein the alloying combination comprises,
approximately,
Cr Up to 0.5
Mo Up to 0.5
W Up to 0.5
V Up to 0.5

Hf Up to 0.5
Nb Up to 0.5.

- [c7] 7. An improved productivity weld wire comprising a sheath encapsulating a steel core having a core fill percent of more than 12%; and the steel core having a composition comprising an alloying element selected from the group consisting of Cr, Mo, V, W, Hf and Nb and combinations thereof, wherein a deposition rate of the weld wire when used during welding increases with the increase of the core fill percent.
- [c8] 8. The improved productivity weld wire of Claim 7, wherein the deposition rate increases from about 15 lb/hr for the core fill percent of about 12% to the deposition rate of about 20 lb/h for the core fill percent of about 30%.
- [c9] 9. The improved productivity weld wire of Claim 7, wherein a total weight percentage of an alloying element does not exceed approximately 1%.
- [c10] 10. The improved productivity weld wire of Claim 8, wherein a total weight percentage of Mo varies from about 0% to about 0.4%.
- [c11] 11. The improved productivity weld wire of Claim 7, wherein the steel core is made of a compacted metal powder.
- [c12] 12. An improved productivity weld wire comprising:
a sheath encapsulating a metal core, wherein a core fill percent of the metal core is higher than 12%; and
the metal core having a composition alloyed with an alloying element or a combination of elements comprising Cr, Mo, V, W, Hf and Nb or combinations thereof, wherein a total weight percentage of the alloying element or the combination of elements in the core composition does not exceed approximately 1%, and wherein a travel speed of the weld wire when used in welding ranges from about 65 in/min to about 145 in/min.
- [c13] 13. The improved productivity weld wire of Claim 12, wherein the travel speed of the wire when used in welding is a maximum travel speed ranging from about

80 in/min to about 145 in/min for the core fill percent ranging from about 12% to about 30 %.

[c14] 14.The improved productivity weld wire of Claim 12, wherein the travel speed of the wire when used in welding increases from about 65 in/min to about 90 in/min.

[c15] 15. The improved productivity weld wire of Claim 13, wherein the maximum travel speed of the wire when used in welding corresponds to the composition comprising a percentage of Mo ranging from about 0% to about 0.4%.

[c16] 16.A method of manufacturing a weld wire comprising:
forming a sheath into a shape which can be filled with a metal powder;
filling the sheath with the metal powder, the metal powder having a composition alloyed with an alloying element or an combination of elements comprising Cr, Mo, V, W, Hf and Nb or combinations thereof, wherein a total weight percentage of the alloying element or the combination of elements in the core composition does not exceed approximately 1%;
compacting the metal powder to form a metal core; and
drawing the wire to achieve a core fill percentage of the metal core no less than 12%.

[c17] 17. The method of Claim 16, wherein the core fill percentage ranges from about 12% to about 30%.

[c18] 18.The method of Claims 17, wherein the alloying element is Mo and wherein the total weight percentage of Mo ranges from about 0% to about 0.4 %.

[c19] 19.The method of Claim 16, wherein the total weight percentage of the combination ranges from about 0.4% to about 0.8%.

[c20] 20.The method of Claim 16, wherein the alloying combination comprises,
approximately,
Cr – Up to 0.5
Mo – Up to 0.5

Nb – Up to 0.5.

1990		1991		1992		1993		1994		1995		1996		1997		1998		1999		2000		2001		2002		2003		2004		2005		2006		2007		2008		2009		2010		2011		2012		2013		2014		2015		2016		2017		2018		2019		2020		2021		2022		2023		2024		2025		2026		2027		2028		2029		2030		2031		2032		2033		2034		2035		2036		2037		2038		2039		2040		2041		2042		2043		2044		2045		2046		2047		2048		2049		2050		2051		2052		2053		2054		2055		2056		2057		2058		2059		2060		2061		2062		2063		2064		2065		2066		2067		2068		2069		2070		2071		2072		2073		2074		2075		2076		2077		2078		2079		2080		2081		2082		2083		2084		2085		2086		2087		2088		2089		2090		2091		2092		2093		2094		2095		2096		2097		2098		2099		2100	
1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100																																																																																																															